

Docket 1999CH006
Serial No. 10/049,219
Group 1714

providing textile piece in an aqueous liquor;
adding (P_s) water-dispersible or -colloidally soluble, end-capped polyesters
as wet-acting lubricants; and
adding a textile treatment agent (T) from aqueous liquor under conditions which would otherwise in the textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate.

19. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to claim 18, wherein: (P_s) is a polyester made from difunctional compounds (D); and monofunctional compounds (E) which are suitable for the end capping of the polyesters, and/or higher oligo-functional compounds (H) which are suitable for the branching of the polyesters.
20. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 18, wherein (P_s) is a polyester (P_s') which is self-dispersible or colloidally soluble in water.
21. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 18, wherein (P_s) is employed in the form of an aqueous, concentrated composition (W).

Docket 1999CH006
Serial No. 10/049,219
Group 1714

22. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 21, wherein (W) is an aqueous composition which is characterised by a content of (P_s) and

(G) a thickening agent.

23. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 21, wherein (W), in addition to (P_s) and optionally (G), contains at least one of the following components:

(X) a non-ionic or anionic emulsifier or a mixture of non-ionic and/or anionic emulsifiers,

(Y) an agent for adjusting the pH

and (Z) at least one formulation additive.

24. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 18, wherein (T) is at least one dye or at least one optical brightener.

25. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 18, in the dyeing or optical brightening of textile material made from polyester fibres, optionally blended with other fibres, in jet dyeing machines.

26. A method for a treatment of textile piece goods from an aqueous liquor under conditions which would otherwise in a textile substrate favour the formation of transport folds and/or the occurrence of friction in or on the substrate according to Claim 18, in the dyeing or optical brightening of textile material made from polyester microfibres, optionally blended with other fibres of comparable fineness
27. Wet-acting lubricant for the dyeing or optical brightening of textile piece goods in rope or tubular form by an exhaust method from aqueous liquor under conditions which would otherwise in textile substrate favour the formation of transport folds or the occurrence of friction in or on the substrate, characterised by a content of (P_S) as defined in Claim 19.
28. Aqueous wet-acting lubricant composition which is an aqueous composition (W) which is defined as in Claim 21.
29. Aqueous wet-acting lubricant composition (W) according to Claim 28, essentially consisting of (P_S) and water and at least one of the additives (G), (X), (Y) and (Z).
30. Process for the production of an aqueous, (G) or/and (X) containing composition (W) according to Claim 29, wherein a melt of (P_S) is mixed in the presence of water with (G) or/and (X) and optionally one or more of (Y) and (Z) is added.
31. Process for the treatment of textile piece goods with a textile treatment agent (T) from aqueous liquor, under conditions which would otherwise in the textile substrate favour the formation of transport folds or the occurrence of friction in or on the substrate, characterised in that the process is carried out in the presence of a water-dispersible or -colloidally soluble, end-capped polyester (P_S), optionally in the form of an aqueous composition (W) as defined in claims 21, as a wet-acting lubricant.

Docket 1999CH006
Serial No. 10/049,219
Group 1714

32. Aqueous polyester composition (W'), essentially consisting of (P_s), (G) and water and optionally at least one of the additives (X), (Y) and (Z), in which (P_s) is as defined as a water-dispersible or -colloidally soluble, end-capped polyester, (G) is defined as a thickening agent, and (X), (Y) and (Z) are as defined in Claim 23.
33. Aqueous polyester composition (W'') according to Claim 32, essentially consisting of (P_s'), (G) and water and additionally optionally one or more of the additives (Y) and/or (Z), in the form of an aqueous dispersion or colloidal solution.
34. Process according to claim 31, wherein (P_s) is removed at the end of the treatment process.